



音博仕科技（惠州）有限公司
Acoustic Professor Tech Co.,Ltd



消费类扬声器
Consumer loudspeaker



工业类扬声器
Industrial type loudspeaker

规格书 SPECIFICATION

技术规范Specification								外观/尺寸图			
产品型号/Model		W01529R-3									
产品分类/Product Category		消费类									
适用场景/Applicable scope		Multi-media/AI									
IP等级/Ip code		/									
额定阻抗/Rated Impedance		4Ω									
最低共振频率 (F0)/Resonance Frequency		150HZ									
额定特性灵敏度/Sound Pressure Level		82dB SPL@1m/W									
有效频率范围/Effective Frequency Range		FO-20KHZ									
额定功率/Rated Noise Power		5W									
最大功率/Long-term Maximum Power		8W									
选择功率/Power Taps		/									
输入电压/Line input		4.47									
额定谐波失真/Distortion		10% Max									
喇叭重量/Weight		30.7g									
安装尺寸/Mounting dimension		/									
产品尺寸/Dimension(L*W*H)(mm)		Ø40mm									
产品规格/Product standard											
面板材质/Surface frame material		/									
网罩材质/Mesh cover material		/									
产品颜色/Color		/									
净重/Unit Weight		/									
总重/Gross Weight		/									
包装尺寸(cm)/Packing Dimension(cm)		/									
扬声器材料规格/Loudspeaker material specifications											
属性分类/Nature		全频扬声器									
音圈规格/Voice coil Specifications		16.28									
DCR阻抗/DCR impedance		4									
音圈骨架/Voice coil bobbin		KSV									
磁钢规格/Magnetic steel specification		15.5*5 N42									
盆架材质/Basin frame material		铁									
鼓纸材质/Cone material		纸									
弹波材质/Elastic wave material		蚕丝									
防尘帽材质/Dust cap material		纸									
T/S参数/The T/S parameter											
Re	Fo	BL	Qms	Qes	Qts	Vas	Mms				
3.6	147	1.971	3.623	0.519	0.454	176.94	605.049				
频响曲线				阻抗曲线				失真曲线			